FLEX　12月度レーンコンディション　KEGEL BUILT FOR BOWLING

Oil Pattern Distance	46	Reverse Brush Drop	35	Oil Per Board	40 ul
Forward Oil Total	14.48 mL	Reverse Oil Total	9.08 mL	Volume Oil Total	23.56 mL
Tank Configuration	A Only	Tank A Conditioner	ICE	Tank B Conditioner	ICE

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	3L	3R	1	10	3	A	35	0.0	0.0	0.0	1400
2	5L	5R	2	10	3	A	62	0.0	2.8	2.8	2480
3	6L	6R	3	14	3	A	87	2.8	8.7	5.9	3480
4	6L	6R	2	14	3	A	58	8.7	12.6	3.9	2320
5	11L	11R	2	18	3	A	38	12.6	17.7	5.1	1520
6	12L	12R	2	18	3	A	34	17.7	22.8	5.1	1360
7	14L	14R	2	22	3	A	26	22.8	29.0	6.2	1040
8	15L	15R	2	22	3	A	22	29.0	35.2	6.2	880
9	15L	15R	0	22	3	A	0	35.2	46.0	10.8	0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	A	0	46.0	33.0	-13.0	0
2	14L	14R	2	22	3	A	26	33.0	26.8	-6.2	1040
3	14L	14R	1	22	3	A	13	26.8	23.7	-3.1	520
4	12L	12R	2	22	3	A	34	23.7	17.5	-6.2	1360
5	10L	10R	2	18	3	A	42	17.5	12.4	-5.1	1680
6	8L	8R	1	18	3	A	25	12.4	9.9	-2.5	1000
7	8L	8R	1	14	3	A	25	9.9	8.0	-1.9	1000
8	6L	6R	1	10	3	A	29	8.0	6.6	-1.4	1160
9	4L	4R	1	10	3	A	33	6.6	5.2	-1.4	1320
10	4L	4R	0	10	3	A	0	5.2	0.0	-5.2	0

Cleaner Ratio Main Mix	NA	Forward	
Cleaner Ratio Back End Mix	NA	Reverse	
Cleaner Ratio Back End Distance	NA	Combined	

Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	5	1.82	1.07	1.07	1.82	5